

Insulation Master® 9000



AUSTRALIAN MADE



INDUSTRIAL GRADE
PERFORMANCE



3 YEARS WARRANTY ON
ENGINE*

This is the fastest way to remove old cellulose insulation fibres from ceiling spaces. Using a large diameter 5 inch duct hose Insulation Master® will rapidly and profitably remove shredded cellulose insulation in a fraction of the time compared with regular vacuum cleaning.

An Australian developed, cellulose and rockwool fibre insulation removal vacuum that solves the design limitations associated with through the impeller style insulation removal machines. Insulation Master® is unique in its class.

Featuring straight-through suction Insulation Master does not pass any of the vacuumed cellulose insulation through its impeller fan scroll housing. This major operational improvement completely eliminates the rapid fan wear and engine drive shaft wear.

As a rapid recovery machine it is perfect for fast and profitable ceiling insulation removal with the benefit of having a significantly longer working lifespan with minimal ongoing maintenance costs. Insulation Master® comes complete including 30 metres of anti-static polyurethane vacuum duct hose. Available as either a skid mount or integrated into a custom road registrable trailer.




HONDA GX630
V TWIN ENGINE



FORKLIFTING
POCKETS



STAINLESS STEEL
CONSTRUCTION



400 LITRE
CAPACITY WITH
BIODEGRADABLE
BAGS



NO
MAINTENANCE
FAN



30MTS VACUUM
HOSE

STANDARD FEATURES

For more info call
+61 3 9769 1211



DIMENSIONS (Skid Only)

Length - 1930mm Width - 700mm Height - 900mm
Weight - 270kg

* Refer to detailed warranty & conditions

Insulation Collection made *easy*

STANDARD & OPTIONAL FEATURES

Extremely high airflow

Unique, high static pressure, 12 blade turbo impeller fan

Honda GX690 engine V-Twin electric key start

Straight through suction means no impeller to snag

Zero abrasion fan wear unlike typical leaf/litter vacuums

Low cost, quick change, 400L capacity collection bags

Ergonomic & light weight vacuum wand

Bags feature inbuilt drawstring closure

Intrinsically safe, fully enclosed rotating impeller fan

Simple to use OH&S safe design

Fully supported

36 Month engine warranty

Robust stainless steel construction

Integrated forklift skid platform

Australian Made

TYPICAL APPLICATIONS

Cellulose and rock wool fiber based insulation
vacuuming



PLEASE NOTE:

This model is not rated to vacuum any type of contaminated, dangerous, asbestos dust. Vacuuming large quantities of any type of dust is not recommended.

OPTIONS



Insulation
removal tool



90-degree inlet
elbow for boom



Additional 400
litre bio
degradable bags



8 x 5 Galvanised
dual axle / single
axle trailer



Cage 600/900mm
With or without
canvas cover